




**50 L/MIN**

**12/24 VDC**



AG-35 pump (12 or 24VDC)


mm (approx.) 120  
 195 150  
 Kg (approx.) 4,30

> **Equivalence boxes**

	FREE	PT-60	PSF-040	PA-60
<b>AG-35 12VDC</b>	53l/min 16A	43l/min 18A	44l/min 18A	34l/min 19A
<b>SAG-35 12VDC</b>	52l/min 17A	34l/min 18A	36l/min 18A	28l/min 19A
<b>AG-35 24VDC</b>	53l/min 7,9A	43l/min 8,5A	44l/min 8,9A	33l/min 9,5A
<b>SAG-35 24VDC</b>	42l/min 8,5A	34l/min 8,9A	36l/min 9,1A	28l/min 9,5A

• CONNECTION: 3/4" - SUCTION: 2,7m 3/4" - DELIVERY: 4m 1"

> **Flow curves**



**AG-35 12VDC**  
**AG-35 24VDC**

0000  
 00010

- **This pump is for the diesel transfer.** It is connected in 12 or 24VDC battery.
- It is suitable for its use on the agriculture, building, public works and industry.
- Suction capacity: of 2,5m from all type of tanks.
- This pump is adaptable to meters, bases, enclosures out in the open or platforms for all type of tanks and it is also adaptable to nozzles, both manuals and automatics.

**TECHNICAL DATA**

- Self-suction - self-priming. Eccentric of self-adjusting blades
- With recirculation bypass
- Suction: 2,5m · Delivery: 20m
- Flow with free outlet: 45-56 l/min
- Consumption: 18-24A (12VDC) and 9-17A (24VDC)
- Motor: 0,30kW (12 and 24VDC) self-ventilated, dust protection
- R.P.M.: 3.000rpm
- Connection through F3/4" threads
- Continuous duty
- 2m cable with clamps
- Stainless steel filter in the suction of 352 micron
- Luminous switch with IP-55 protection

**DIESEL BATTERY KIT 12VDC**  
**DIESEL BATTERY KIT 24VDC**

14190  
 14200

- **Kit with the necessary elements to transfer diesel through 12 or 24VDC pump.**
  - **Easy installation**
- Composed of:
- AG-35 12 or 24VDC pump
  - PSF-040 - Manual aluminium nozzle with F1" swivel and curved end
  - 4m antistatic delivery hose Ø19mm double layer, special for diesel, with adapters in both ends
  - PP Lower filter with STAINLESS mesh, 2 brackets 23 x 35, brass elbow 90° MF 3/4" and adapter 3/4" PP
  - It is supplied in a printed box, with EAN-13 bar code



mm (approx.) 165  
 347 350  
 Kg (approx.) 7,50

➤ **SAG-35 - PUMP WITH LITRE METER**

- Kit composed of pump with litre meter
- It can be assembled on a metal base



Pump		Meters			Base	
AG-35 12VDC	AG-35 24VDC	MG-80 Mechanical	MGE-80 Electronic	MGE-80 RI-97 Electronic with control frame	Metallic nr. 3	
•		•				31010
	•	•				31000
		•			•	30010
	•	•			•	30130
•			•			31270
	•		•			31280
•			•		•	30410
	•		•		•	30420
•				•		31291
	•			•		31301
•				•	•	30431
	•			•	•	30441

➤ **HORIZONTAL KITS WITH AG-35 PUMP**

The horizontal kits are equipped with:

- AG-35 12 or 24VDC pump (with or without mechanical meter)
- Manual or automatic nozzle

\*Accessories:

- 3m antistatic delivery hose Ø19mm double layer, special for diesel, with adapters in both ends
- 1,70m elbow hose Ø21mm special for diesel
- M3/4" x 26PP Adapter
- 2 brackets 23 x 35
- PP lower filter



Pump		Accessories	Meters	Nozzles		
AG-35 12VDC	AG-35 24VDC	*	MG-80 Mechanical	PSF-040 Manual	PA-60 Automatic (with swivel built-in)	
•		•		•		14000
	•	•		•		14010
		•		•	•	14060
	•	•		•	•	14070
•		•	•	•		14500
	•	•	•	•		14510
•		•	•		•	14740
	•	•	•	•	•	14750

➤ **VERTICAL KITS WITH TELESCOPIC TUBE AND AG-35 PUMP**

The vertical kits are equipped with:

- AG-35 12 or 24VDC pump (with or without mechanical meter)
- Manual or automatic nozzle

\*Accessories:

- M3/4" F1" telescopic tube kit, height 1,90m, with filter built-in
- 4m antistatic delivery hose Ø19mm double layer, special for diesel with adapters in both ends



Pump		Accessories	Meters	Nozzles		
AG-35 12VDC	AG-35 24VDC	*	MG-80 Mechanical	PSF-040 Manual	PA-60 Automatic (with swivel built-in)	
•		•		•		15000
	•	•		•		15010
		•		•	•	15060
	•	•		•	•	15070
•		•	•	•		15500
	•	•	•	•		15510
•		•	•		•	15650
	•	•	•	•	•	15660